



**NEW**  
**5 WINGS ROTOR**  
**FOR MORE POWER**  
**NEW GEARS**  
**1300 RPM**

# FP702

## NEW PNEUMATIC HAND SHEAR

New FP702. The new cutting solution. Suitable for leather.



1946



1946

### WHAT'S NEW:

New 5 wings turbine  
New gears 1300 rpm  
New housing coating for heat reducing  
High manageability in 920 g

### FOLLOW US:



### RASOR ELETTROMECCANICA SRL

Via Vincenzo Caldesi 6 • 20161 Milan • Italy  
ph. +39 02 66 22 12 31 • fax +39 02 66 22 12 93  
info@rasor-cutters.com

www.rasor-cutters.com



# NEW PNEUMATIC HAND SHEAR CE FP702



### TECHNICAL DETAILS:

Muffled turbine motor with central back-located air exhaust  
6 bar nominal\* ( $\pm 1$  bar) lubricated air supply  
**Air consumption:** 9 std liters/sec\*  
**Power:** 380 W at nominal air supply conditions  
**Blade:** 70 mm with hard metal counterblade  
**Blade descr.:** 70EHSS, 70 mm dia., 6-edge, HSS steel  
**Blade speed:** 1300 r.p.m.\*  
**Cutting ability:** up to 20 mm  
**Sound pressure:** 72 dBe (EN ISO 15744)\*  
**Vibration Level:** 1,36 m/sec<sup>2</sup> (ISO 8662)\*  
**Net weight:** 920 g  
**Total weight (with packing):** 1750 g  
**Temperature range:** 0 – 55 C  
**Umidity range:** 10 – 95% without condensate

*\*The reported data are collected at a pressure of 6 bar (ISO 2787: 1984), recommended operating pressure.*



Minimum recommended



Rasor recommend to use only dry air lubricated with special Rasor VG 10 pneumatic oil



### BLADES AVAILABLE:

**70SHSS**, 70 mm 4-edges, HSS steel | **70EHSS**, 70 mm 6-edges, HSS steel | **70CHSS**, 70 mm circular, HSS steel | **70DHSS**, 70 mm 10-edges, HSS steel | **70SHSSTF**, 70 mm 4-edges, HSS steel Teflon<sup>®</sup> coated | **70EHSSTF**, 70 mm 6-edges, HSS steel Teflon<sup>®</sup> coated | **70EMD**, 70 mm 6-edges, Carbide (Widia<sup>®</sup>) | **70DHSSTN**, 70 mm 10-edges, HSS steel Titanium coated | **70DHSSTF**, 70 mm 10-edges, HSS steel Teflon<sup>®</sup> coated